



TYM T255
WITH AGRICULTURAL TYRES

Product image shown for illustration only

T255

SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, range of diesel engines available from 19 to 75hp mean these superb workhorses can cover a wide variety of grounds care tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, foldable ROPS, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While all models can be fitted with optional loaders.

**FREE ONSITE
DEMONSTRATION**

CALL TODAY

Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.

MODEL

ENGINE

Manufacturer	Yanmar
Model	3TNV76-UD
Engine HP (kw)-gross	25.3 (18.9)
Rated engine speed	3000
Number of cylinders	3
Displacement-cu.in. (cc)	68.1 (1116)
Air cleaner	Single dry

ELECTRICAL SYSTEM

Alternator	12V, 40A
------------	----------

FUEL SYSTEM

Type	Indirect fuel injection
------	-------------------------

DRIVETRAIN

Transmission type	HST
Number of speeds	Infinite / 2 Range
Max travelling speed, mph (km/h)	10.5 (16.9)
Brakes	Wet disc
Steering	Hydrostatic
Clutch	Dry single plate

HYDRAULIC SYSTEM

Pump (type)	Single gear pump with flow divider
Implement pump cap. gpm (L/min)	4.18 (15.8)
Steering pump cap. gpm (L/min)	2.77 (10.5)
Maximum total flow gpm (L/min)	6.95 (26.3)
Category, 3-point hitch	1 (N)
Hitch lift capacity, lb. (kg)	1323 (600)
at 24 inches behind link ends, lb. (kg)	1058 (480)
Lift control type	Position
Joystick valve	N/A
No. of standard remote valves-option	1

PTO

Type	Independent
Control	Electric/Hydro
Mid (rpm)	2000
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

CAPACITIES

Fuel tank, U.S. gal. (L)	5.81 (22)
Cooling system U.S. qt. (L)	3.8 (3.6)
Crankcase (with filter) U.S. qt. (L)	2.9 (2.7)
Trans. & hydr. system, U.S. gal. (L)	3.7 (14)
Front axle qt. (L)	3.7 (3.5)

DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P	100.5 (2553)
Overall width, in. (mm)	45.8 (1164)
Wheelbase, in. (mm)	57.5 (1460)
Height to top of ROPS, in. (mm)	91.3 (2320)
Min. ground clearance, in. (mm)	9.4 (240)
Min. turning radius, in. (mm) with brakes	-
Min. turning radius, in. (mm) w/o brakes	100 (2540)

STANDARD TYRES

Agricultural front	6-12
Agricultural rear	9.5-16
Turf front	20x8-15
Turf rear	29x12.5-15
Industrial front	20x8-10
Industrial rear	27x12.5-15

ROLL-OVER PROTECTIVE STRUCTURES

Standard	ROPS (Rear)
----------	-------------

WEIGHT

Total weight, lb. (kg)	1693 (768)
------------------------	------------

T255 HST

OPTIONAL LOADER

MODEL

Fits Tractor Model	T255
Maximum Lift Height	1912 mm
Clearance with Attachment Level	1745 mm
Clearance with Attachment Dumped	1458 mm
Reach at Maximum Height	633 mm
Maximum Dump Angle	38°
Reach with Attachment on Ground	1302 mm
Attachment Roll Back Angle	22°
Digging Depth Below Grade	104 mm
Overall Height in Carry Position	1088 mm
Depth of Attachment (to back of inner shelf)	480 mm
Height of Attachment	461 mm
Depth of Attachment (to pivot pin)	523 mm
Lift Capacity at Full Height at Pivot Pins	328 kg
Breakout Force at Ground Level, Pivot Pins	540 kg
Boom Raising Time	4.4 sec
Boom Lowering Time	2.5 sec
Bucket Rollback Time	3.8 sec
Bucket Dumping Time	5.3 sec
Attachment Used for Specification	1270 mm
Bucket Capacity	5.3 ft ³
Parallel Lift	N/A
3rd Function	N/A
Front Bucket	Bobcat Fitment

TX25P

Fits Tractor Model	T255
Maximum Lift Height	1912 mm
Clearance with Attachment Level	1745 mm
Clearance with Attachment Dumped	1458 mm
Reach at Maximum Height	633 mm
Maximum Dump Angle	38°
Reach with Attachment on Ground	1302 mm
Attachment Roll Back Angle	22°
Digging Depth Below Grade	104 mm
Overall Height in Carry Position	1088 mm
Depth of Attachment (to back of inner shelf)	480 mm
Height of Attachment	461 mm
Depth of Attachment (to pivot pin)	523 mm
Lift Capacity at Full Height at Pivot Pins	328 kg
Breakout Force at Ground Level, Pivot Pins	540 kg
Boom Raising Time	4.4 sec
Boom Lowering Time	2.5 sec
Bucket Rollback Time	3.8 sec
Bucket Dumping Time	5.3 sec
Attachment Used for Specification	1270 mm
Bucket Capacity	5.3 ft ³
Parallel Lift	N/A
3rd Function	N/A
Front Bucket	Bobcat Fitment

DEALER STAMP

