



TYM T395
WITH AGRICULTURAL TYRES

Product image shown for illustration only

T395

SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. powerful, reliable range of diesel engines available from 19 to 75hp mean these superb workhorses can cover a wide variety of grounds care tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While all models can be fitted with optional loaders.

Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.

**FREE ONSITE
DEMONSTRATION**

CALL TODAY



MODEL	T395	T395 CAB	T395 HST	T395 CAB HST
ENGINE				
Manufacturer	Yanmar	Yanmar	Yanmar	Yanmar
Model	3TNV88C-D	3TNV88C-D	3TNV88C-D	3TNV88C-D
Engine HP (kw)-gross	36.9 (27.5)	36.9 (27.5)	36.9 (27.5)	36.9 (27.5)
Rated engine speed	3000	3000	3000	3000
Number of cylinders	3	3	3	3
Displacement-cu.in. (cc)	100.2 (1642)	100.2 (1642)	100.2 (1642)	100.2 (1642)
Air cleaner	Dual dry	Dual dry	Dual dry	Dual dry
ELECTRICAL SYSTEM				
Alternator	12V, 55A	12V, 55A	12V, 55A	12V, 55A
FUEL SYSTEM				
Type	CRDI	CRDI	CRDI	CRDI
DRIVETRAIN				
Transmission type	Sync/Shuttle	Sync/Shuttle	HST	HST
Number of speeds	12/F 12/R	12/F 12/R	Infinite/3 Range	Infinite/3 Range
Max travelling speed, mph (km/h)	15 (24.2)	15 (24.2)	17.9 (28.9)	17.9 (28.9)
Brakes	Wet disc	Wet disc	Wet disc	Wet disc
Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Clutch	Dry single plate	Dry single plate	N/A	N/A
HYDRAULIC SYSTEM				
Pump (type)	Dual gear pump	Dual gear pump	Dual gear pump	Dual gear pump
Implement pump cap. gpm (L/min)	6.3 (23.9)	6.3 (23.9)	6.3 (23.9)	6.3 (23.9)
Steering pump cap. gpm (L/min)	4.3 (16.2)	4.3 (16.2)	4.6 (17.3)	4.6 (17.3)
Maximum total flow gpm (L/min)	10.6 (40.1)	10.6 (40.1)	10.9 (41.2)	10.9 (41.2)
Category, 3-point hitch	I	I	I	I
Hitch lift capacity, lb. (kg)	2646 (1200)	2646 (1200)	2646 (1200)	2646 (1200)
at 24 inches behind link ends, lb. (kg)	1764 (800)	1764 (800)	1764 (800)	1764 (800)
Lift control type	Position/Draft	Position	Position	Position
Joystick valve	Standard	Standard	Standard	Standard
No. of standard remote valves-option	2	2	1	1
PTO				
Type	Independent	Independent	Independent	Independent
Control	Electric/Hydro	Electric/Hydro	Electric/Hydro	Electric/Hydro
Mid (rpm) option	N/A	N/A	2000	2000
Rear (rpm)	540	540	540	540
Shaft diameter in. (mm)	13/8 (35)	13/8 (35)	13/8 (35)	13/8 (35)
CAPACITIES				
Fuel tank, U.S. gal. (L)	9.0 (34)	9.0 (34)	9.0 (34)	9.0 (34)
Cooling system U.S. qt. (L)	7.4 (7)	7.4 (7)	7.4 (7)	7.4 (7)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)	6.0 (5.7)	6.0 (5.7)	6.0 (5.7)
Trans. & hydr. system, U.S. gal. (L)	8.5 (32)	8.5 (32)	9.25 (35)	9.25 (35)
Front axle qt. (L)	8.7 (8.2)	8.7 (8.2)	8.7 (8.2)	8.7 (8.2)
DIMENSIONS (with standard tyres)				
Overall length, in. (mm) with 3P	126 (3200)	1238 (3250)	126 (3200)	1238 (3250)
Overall width, in. (mm)	53.5 (1360)	58.0 (1475)	53.5 (1360)	58.0 (1475)
Wheelbase, in. (mm)	64.5 (1640)	66.9 (1700)	66.1 (1680)	66.1 (1680)
Height to top of ROPS, in. (mm)	94.5 (2400)	92.5 (2350)	94.5 (2400)	92.5 (2350)
Min. ground clearance, in. (mm)	12.8 (325)	12.8 (325)	13.8 (350)	13.8 (350)
Min. turning radius, in. (mm) with brakes	94.4 (2400)	94.4 (2400)	94.4 (2400)	94.4 (2400)
Min. turning radius, in. (mm) w/o brakes	116 (2950)	116 (2950)	116 (2950)	116 (2950)
STANDARD TYRES				
Agricultural front	8.0-16	8.0-16	8.0-16	8.0-16
Agricultural rear	12.4-24	12.4-24	12.4-24	12.4-24
Turf front	27x10.50-15	27x10.50-15	27x10.50-15	27x10.50-15
Turf rear	41x14.00-20	41x14.00-20	41x14.00-20	41x14.00-20
Industrial front	27-10.5-15	27-10.5-15	27-10.5-15	27-10.5-15
Industrial rear	12.5-20	12.5-20	12.5-20	12.5-20
ROLL-OVER PROTECTIVE STRUCTURES				
Standard	ROPS (Front/Rear)	Cab	ROPS (Front/Rear)	Cab
WEIGHT				
Total weight, lb. (kg)	3128 (1419)	3472 (1575)	3128 (1419)	3472 (1575)

OPTIONAL LOADER

MODEL	TX39H
Fits Tractor Model	T395
Maximum Lift Height	2598 mm
Clearance with Attachment Level	2380 mm
Clearance with Attachment Dumped	1976 mm
Reach at Maximum Height	589 mm
Maximum Dump Angle	50°
Reach with Attachment on Ground	1699 mm
Attachment Roll Back Angle	30°
Digging Depth Below Grade	112 mm
Overall Height in Carry Position	1412 mm
Depth of Attachment (to back of inner shelf)	579 mm
Height of Attachment	564 mm
Depth of Attachment (to pivot pin)	754 mm
Lift Capacity at Full Height at Pivot Pins	960 kg
Breakout Force at Ground Level, Pivot Pins	1558 kg
Attachment Used for Specification	1575 mm
Bucket Capacity	10.4 ft ³
Parallel Lift	N/A
3rd Function	Included
Front Bucket	Bobcat Fitment

DEALER STAMP



Reesink UK LTD, 1-3 Station Road, St. Neots, Cambridgeshire PE19 1QF
T 01480 226800 E info@reesinkturfcare.co.uk W reesinkturfcare.co.uk
 Reesink Ireland LTD, Kilboggan, Nurney, Co. Kildare R51 NY22
T 045 241963 E info@reesinkturfcare.ie

